

AUDIT TRAIL ACCESS OPTIONS



AL-IR1 Infrared Printer:
 Optional hand-held infrared printer may be used to print the event log and user code list.






AL-DTM Data Transfer Module:
 Module used to program multiple DL-3000 locks. The AL-DTM can also be used to collect log information from up to 48 DL-3000 locks before returning to PC.



DL-WINDOWS SOFTWARE:
 Alarm Lock's own (optional) Windows-format software for easy programming, scheduling and log viewing.

AL-PCI: PC interface cable interconnects lock and PC for up/downloaded data transmission (programming & Audit Trail information).

ORDERING INFORMATION

 T3 WP Lever US3 DL3000WP/3	 T3 IC Lever US26D DL3000IC/26D
DL 30 00 WP IC /26D -Y	
<p>Model & Series: DL30 = Trilogy T3 Series</p> <p>Trim: 00 = Straight Lever 75 = Regal Lever</p> <p>Exterior / Interior Use: WP = Weatherproof for exterior use (Note: No "WP" indicates standard, interior use.)</p> <p>Cylinder: IC = Standard Interchangeable Core Prep for Best, Falcon, Arrow, KSP (Note: No "IC" indicates standard K.O. cylinder.)</p>	
<p>Finish: /3 = US3 Polished Brass /26 = US26 Polished Chrome /26D = US26D Satin Chrome /5 = US5 Antique Brass /10B = Duronodic (Special Order)</p> <p>Special Order IC Prep: -Y = Yale -M = Medeco -R = Sargent -C = Corbin/Russwin -S = Schlage</p>	
	

ALARM LOCK SYSTEMS, Inc. • A Division of the NAPCO Security Group
 345 Bayview Avenue • Amityville, NY • 11701 • USA
 1-800-AL-LOCK (252-5625) • 631-789-4871 • Fax: 631-789-3383
www.alarmlock.com

NAPCO Group Europe Limited
 224 Europa Boulevard, Gerrard Business Park • Warrington WA5 5TN England
 +44 (0) 1925 242428 • Fax: +44 (0) 1925 242429 • www.napcosecurity.com

Trilogy® is a registered trademark of Alarm Lock. ©Alarm Lock, 2009. Patents Pending.



AL144A

DL3000 Series

*Standalone Access Control Systems With Audit Trail Feature
 For Indoor And Outdoor Applications.*



FEATURES

- Clutch mechanism insures long life & durability
- 150 scheduled events, including 4 "quick schedules" for programming the 4 most common time schedules in one step
- 300 user codes including: Master, Manager, Supervisor and Basic User. Also one-time entry Service Code
- Times entry allowance from 5-15 seconds
- Audit Trail with Time/Date Stamp for a printable record of all electronic activity
- Real Time Clock allows logging of events to within 1 second of accuracy
- Relay may be programmed to energize when one or more selected events occur
- 4 Time-Out functions allow a user to enable other users or unlock the lock for some time period without needing to return to the lock
- 1600 Event Log
- Easy to install. Retrofits most cylindrical locksets and digital locks
- Battery operated; uses 5 AA batteries
- Available in standard key override and interchangeable core models accepting 6 or 7 pin cores from Arrow, Best, Falcon or KSP. Other IC core preps available.
- Available in standard Trilogy leverset (straight) or with new Regal (curved) lever shown.



Regal Handle Trim

WEATHERPROOF MODELS

- Dual water-sealed keypad, with silicon outerseal and mylar innerseal for extra protection
- Weatherproof battery holder
- Completely encapsulated circuit board hermetically sealed against the elements
- Comprehensively tested to be rated for direct water exposure
- Operational temperature range of +151°F to -20°F (+66°C to -29°C)

(Note: all Trilogy models are available in WP weatherproof and non-WP standard models for interior doors.)



SPECIFICATIONS

OPERATION: Clutch mechanism permits turning lever without retracting latch and reduces stress on lock bodies and spindle. Outside lever free turning in locked position. Entering access code, key bypass, or remote bypass will allow lever to retract latch. Inside lever always instant egress.

DOOR THICKNESS: 1 1/2" to 1 7/8". Other thicknesses. Please consult factory.

BACKSET: 2 1/2" Standard. 2 3/8" backset also available.

KEYPAD: All metal, 12 button programmable for multi-level access functions including group or individual user codes, master and management codes, pass and emergency or service code, lockout and remote override capability and allowable entry time from 5 to 15 seconds.

STANDARD KEY OVERRIDE CYLINDERS: Solid brass 6 pin tumbler cylinder pinned 5, SC1 keyway, furnished in all locks. Additional tailpieces included: HW580 fits Schlage, Corbin/Russwin CL, Sargent 480 Series, ASSA65-611. Model HW620 fits Ilco and Lort cylinders.

AUDIT TRAIL: Entry activity log can be polled to the Data Transfer Module (AL-DTM), any PC using DL-Windows Software, and/or can be on-site printed using the hand-held infrared printer (AL-IR1). Activities included are: unlock/lock events, program mode changes, user entry, keypad lockout, remote release events, unauthorized code attempts, etc.

INTERCHANGEABLE CORE MODELS: Accepts 6 & 7 Pin Cylinders from: Best, Arrow, KSP, Medeco Keymark & Kaba Peaks. Also available IC Core models for Yale, Medeco, Sargent, Corbin/Russwin CL and Schlage. *Alarm Lock Tailpiece is supplied. IC Core is not included.*

LATCHBOLT: UL Listed, fire rated, 3 hours, 1/2" throw, solid brass, deadlocking. Reversible. Adjustable front for flat or beveled doors.

STRIKE: 1 1/2" x 2 1/4" T strike & 1 1/4" x 4 1/4" ASA strike included. With screws for wood or metal jams.

LATCH FRONT: 1 1/2" x 2 1/4" wrought brass or stainless steel.


HANDING: Non-handed.

FINISHES: US3 polished brass, US26D satin chrome, US26 polished chrome, US5 antique brass, 10B Duronodic. (Other finishes available, consult factory.)

POWER: 5 AA alkaline batteries, supplied. Audible low battery alert, visual and audible entry indicators, unique Flex Drive® motor. 100,000 cycles typical.

DOOR PREP: Standard ANSI A115 Series Prep, modified by adding additional through-bolt holes.

COMPLIANCES: Grade I, heavy duty cylindrical lockset, UL listed to the IOC Positive Pressure Specification and FCC certified. ADA compliant levers.



Interchangeable Core Option
Special IC Core Preps available

